MF MC6


MultiFaster 6 lines, size 04. ISO 16028 individual couplings connectable.


Thanks to the special cartridges design, it's possible to connect to each plate either its counterpart or individual ISO 16028 quick couplings 1/4".




Applications









Technical Specifications

					_	Ві	Burst pressure (MPa)		
dash	Size mm	inch	Working Pressure (MPa)	Flow Rate (I/min)	Spillage (ml)	Male	Female	Male + Female	
04	6,3	1/4"	20	25	0,008	80	80	80	

Material	Aluminium; Steel
Seals	NBR; PUR
Working temperatures	- 25 °C to + 100 °C
Surface treatment	MATE 500 (CrIII); Paint

Valve Type	Flat
Connection	Lever
Disconnection	Lever
Connection Under Pressure	Allowed Residual

MC6

	Size				Thread Type					FIXED
dash	mm	inch	Housing	Number of Couplings	Thread Type	Standard	Thread	Electrical Connector N Type		Part Number
04	6,3	1/4"	6	6	0/ SAE	ISO 11926-1	9/16" - 18 UNF FEMALE ORB			MC6-04-38S FC

	Size							MOBILE		
dash	mm	inch	Housing	Number of Couplings	Thread Type	Standard	Thread	Electrical Connector N Type		Part Number
04	6,3	1/4"	6	6	0/ SAE	ISO 11926-1	9/16" - 18 UNF FEMALE ORB			MC6-04-38S MC